

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

- Trade name: **Ijmocolor EP**
- Article number: 301
- UFI: HMR2-60K0-P001-6SVP
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- Sector of Use
 - SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
 - SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
 - SU19 Building and construction work
- Process category PROC19 Manual activities involving hand contact
- Environmental release category
 - ERC5 Use at industrial site leading to inclusion into/onto article
 - ERC8c Widespread use leading to inclusion into/onto article (indoor)
 - ERC8f Widespread use leading to inclusion into/onto article (outdoor)
 - AC13 Plastic articles
- Article category
- Application of the substance / the mixture
 - See our technical datasheet for application details of this product.
 - Pigment

1.3 Details of the supplier of the safety data sheet


- Manufacturer/Supplier: De IJssel Coatings BV, Centrumbaan 960, NL 2841 MH Moordrecht
Tel: +31 182 372177, E-mail: info@de-ijssel-coatings.nl
- Further information obtainable from: Research and Development.


1.4 Emergency telephone number:

De IJssel Coatings BV, Tel. +31 182 372177, E-mail: safety@de-ijssel-coatings.nl
 Office hours: working days from 08:00 to 17:00 hrs.



SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

- Classification according to Regulation (EC) No 1272/2008
-  GHS09 environment
- Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

-  GHS07
- Skin Irrit. 2 H315 Causes skin irritation.
- Eye Irrit. 2 H319 Causes serious eye irritation.
- Skin Sens. 1 H317 May cause an allergic skin reaction.

2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.
- Hazard pictograms   GHS07 GHS09
- Signal word Warning
- Hazard-determining components of labelling: bis[4-(2,3-epoxypropoxy)phenyl]propane reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)
1,6-bis(2,3-epoxypropoxy)hexane
- Hazard statements H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.
- Precautionary statements
 - P261 Avoid breathing mist/vapours/spray.
 - P273 Avoid release to the environment.
 - P280 Wear protective gloves / eye protection / face protection.
 - P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - P362+P364 Take off contaminated clothing and wash it before reuse.
 - P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 - P337+P313 If eye irritation persists: Get medical advice/attention.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 18.07.2023

Version number 52 (replaces version 51)

Revision: 13.06.2023

Trade name: IJmocolor EP

(Contd. of page 1)

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Labelling of packages where the contents do not exceed 125 ml
- Hazard pictograms



GHS07 GHS09

- Signal word
- Hazard-determining components of labelling:

Warning

- Hazard statements
- Precautionary statements

bis[4-(2,3-epoxypropoxy)phenyl]propane
reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)
1,6-bis(2,3-epoxypropoxy)hexane
H317 May cause an allergic skin reaction.
P261 Avoid breathing mist/vapours/spray.
P280 Wear protective gloves / eye protection / face protection.
P362+P364 Take off contaminated clothing and wash it before reuse.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients**3.2 Mixtures**

- Description: Mixture of substances listed below with nonhazardous additions.

- Dangerous components:

CAS: 1675-54-3 EINECS: 216-823-5 Index number: 603-073-00-2 Reg.nr.: 01-2119456619-26	bis[4-(2,3-epoxypropoxy)phenyl]propane ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Specific concentration limits: Eye Irrit. 2; H319: C \geq 5 % Skin Irrit. 2; H315: C \geq 5 %	25 – 50%
CAS: 9003-36-5 NLP: 500-006-8 Reg.nr.: 01-2119454392-40	reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700) ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317, EUH205	3 – 10%
CAS: 933999-84-9 EC number: 618-939-5 Reg.nr.: 01-2119463471-41	1,6-bis(2,3-epoxypropoxy)hexane ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	3 – 10%

- Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

(Contd. on page 3)

Trade name: IJmocolor EP

(Contd. of page 2)

- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:** Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

*** SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire - and explosion protection: No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- Storage: Requirements to be met by storerooms and receptacles: Store material in original, tightly closed containers in a cool, well-ventilated area in accordance with applicable (local) regulations. Depending on total volume stored, the storage area should comply with PGS15.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- Recommended storage temperature: 5 - 30 °C
- **7.3 Specific end use(s)** No further relevant information available.

*** SECTION 8: Exposure controls/personal protection**

- **8.1 Control parameters**
- Ingredients with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNEL (Derived No Effect Level) for workers		
1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane		
Dermal	Long-term - systemic effects, worker	0.75 mg/kg bw/day (Worker)
Inhalative	Long-term - systemic effects, worker	4.93 mg/m ³ (Worker)
9003-36-5 reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)		
Dermal	Acute - local effects, worker	8.3 µg/cm ² (Worker)
	Long-term - systemic effects, worker	104.15 mg/kg bw/day (Worker)
Inhalative	Long-term - systemic effects, worker	29.39 mg/m ³ (Worker)
933999-84-9 1,6-bis(2,3-epoxypropoxy)hexane		
Dermal	Long-term - systemic effects, worker	2.8 mg/kg bw/day (Worker)
	Long term - local effects, worker	22.6 µg/cm ² (Worker)

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 18.07.2023

Version number 52 (replaces version 51)

Revision: 13.06.2023

Trade name: IJmocolor EP

(Contd. of page 3)

Inhalative	Long-term - systemic effects, worker	10.57 mg/m ³ (Worker)
	Long-term - local effects, worker	0.44 mg/m ³ (Worker)

· DNEL (Derived No Effect Level) for the general population

1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane

Oral	Long-term - systemic effects, general population	0.5 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects, general population	0.0893 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects, general population	0.87 mg/m ³ (General population)

9003-36-5 reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

Oral	Long-term - systemic effects, general population	6.25 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects, general population	62.5 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects, general population	8.7 mg/m ³ (General population)

933999-84-9 1,6-bis(2,3-epoxypropoxy)hexane

Oral	Acute - systemic effects, general population	0.83 mg/kg bw/day (General population)
	Long-term - systemic effects, general population	0.83 mg/kg bw/day (General population)
Dermal	Acute - systemic effects, general population	1.7 mg/kg bw/day (General population)
	Acute - local effects, general population	13.6 µg/cm ² (General population)
Inhalative	Long-term - systemic effects, general population	1.7 mg/kg bw/day (General population)
	Long-term - local effects, general population	13.6 µg/cm ² (General population)
Inhalative	Acute - systemic effects, general population	2.9 mg/m ³ (General population)
	Long-term - systemic effects, general population	2.9 mg/m ³ (General population)
	Long-term - local effects, general population	0.27 mg/m ³ (General population)

· PNEC (Predicted No Effect Concentration) values

1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane

Aquatic compartment - freshwater	0.006 mg/l (Freshwater)
Aquatic compartment - marine water	0.001 mg/l (Marine water)
Aquatic compartment - sediment in freshwater	0.341 mg/kg sed dw (Sediment freshwater)
Aquatic compartment - sediment in marine water	0.034 mg/kg sed dw (Sediment marine water)
Terrestrial compartment - soil	0.065 mg/kg dw (Soil)
Sewage treatment plant	10 mg/l (stp)
Oral secondary poisoning	11 mg/kg food (Food sec poisoning)

9003-36-5 reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

Aquatic compartment - freshwater	0.003 mg/l (Freshwater)
Aquatic compartment - marine water	0.0003 mg/l (Marine water)
Aquatic compartment - water, intermittent releases	0.0254 mg/l (Intermittent release water)
Aquatic compartment - sediment in freshwater	0.294 mg/kg sed dw (Sediment freshwater)
Aquatic compartment - sediment in marine water	0.0294 mg/kg sed dw (Sediment marine water)
Terrestrial compartment - soil	0.237 mg/kg dw (Soil)
Sewage treatment plant	10 mg/l (stp)

933999-84-9 1,6-bis(2,3-epoxypropoxy)hexane

Aquatic compartment - freshwater	0.0115 mg/l (Freshwater)
Aquatic compartment - marine water	0.0015 mg/l (Marine water)
Aquatic compartment - water, intermittent releases	0.115 mg/l (Intermittent release water)
Aquatic compartment - sediment in freshwater	0.283 mg/kg sed dw (Sediment freshwater)
Aquatic compartment - sediment in marine water	0.283 mg/kg sed dw (Sediment marine water)

· Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove all soiled and contaminated clothing
 - Wash hands before breaks and at the end of work.
 - Avoid contact with the eyes and skin.
- Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 52 (replaces version 51)

Revision: 13.06.2023

Trade name: IJmocolor EP

(Contd. of page 4)

<ul style="list-style-type: none"> · Hand protection · Material of gloves · Penetration time of glove material · For the permanent contact gloves made of the following materials are suitable: · As protection from splashes gloves made of the following materials are suitable: · Not suitable are gloves made of the following materials: · Eye/face protection 	<p>Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation</p> <p>Nitrile rubber, NBR The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Recommended thickness of the material: ≥ 0.3 mm</p> <p>The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).</p> <p>Nitrile rubber, NBR</p> <p>Nitrile rubber, NBR</p> <p>Leather gloves Strong material gloves Tightly sealed goggles</p>
--	--

*** SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties	
· General Information	
· Physical state	Fluid
· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	Undetermined.
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	> 150 °C (Pensky Martens, ASTM D93)
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C:	1.766 g/cm ³ (DIN 51757, ASTM D 1298)
· Relative density	Not determined.
· Vapour density	Not determined.
· 9.2 Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· VOC:	
· VOC (2004/42/EC):	0.00 %

(Contd. on page 6)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 52 (replaces version 51)

Revision: 13.06.2023

Trade name: IJmocolor EP

(Contd. of page 5)

· Solids content:	100.0 %
· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

*** SECTION 11: Toxicological information**

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values relevant for classification:

Components	Type	Value	Species
9003-36-5 reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)			
Oral	LD50	23,800 mg/kg	(Rat)
Dermal	LD50	> 2,000 mg/kg	(Rabbit)
933999-84-9 1,6-bis(2,3-epoxypropoxy)hexane			
Oral	LD50	2,900 mg/kg	(Rat)
Dermal	LD50	> 4,900 mg/kg	(Rat)

- Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

· **11.2 Information on other hazards**

· Endocrine disrupting properties	
None of the ingredients is listed.	

(Contd. on page 7)

Trade name: IJmocolor EP

(Contd. of page 6)

*** SECTION 12: Ecological information**

- **12.1 Toxicity**
- Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- PBT: Not applicable.
- vPvB: Not applicable.
- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- Remark: Toxic for fish
- Additional ecological information:
- General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.
 Also poisonous for fish and plankton in water bodies.
 Toxic for aquatic organisms

*** SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**
- Recommendation: Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue	
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 99	wastes not otherwise specified
HP4	Irritant - skin irritation and eye damage
HP13	Sensitising
HP14	Ecotoxic

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN number or ID number	
· ADR/RID/ADN, IMDG, IATA	UN3082
· 14.2 UN proper shipping name	
· ADR/RID/ADN	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl]propane, reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700))
· IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl]propane, reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)), MARINE POLLUTANT
· IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl]propane, reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700))
· 14.3 Transport hazard class(es)	
· ADR/RID/ADN	
· Class	9 (M6) Miscellaneous dangerous substances and articles.
· Label	9

(Contd. on page 8)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 52 (replaces version 51)

Revision: 13.06.2023

Trade name: IJmocolor EP

(Contd. of page 7)

· IMDG, IATA · Class · Label	9 Miscellaneous dangerous substances and articles. 9
· 14.4 Packing group · ADR/RID/ADN, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR/RID/ADN): · Special marking (IATA):	Product contains environmentally hazardous substances: bis[4-(2,3-epoxypropoxy)phenyl]propane Yes Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category	Warning: Miscellaneous dangerous substances and articles. 90 F-A,S-F A
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information: · ADR/RID/ADN · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code	 5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3 (-)
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BIS[4-(2,3-EPOXYPROPOXY)PHENYL]PROPANE, REACTION PRODUCT: BISPHENOL-F-(EPICHLORHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700)), 9, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I
None of the ingredients is listed.
- Seveso category
E2 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements
200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements
500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII
Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

(Contd. on page 9)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 52 (replaces version 51)

Revision: 13.06.2023

Trade name: IJmocolor EP

(Contd. of page 8)

· Regulation (EC) No 273/2004 on drug precursors	None of the ingredients is listed.
· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors	None of the ingredients is listed.
· 15.2 Chemical safety assessment:	A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
 - H315 Causes skin irritation.
 - H317 May cause an allergic skin reaction.
 - H319 Causes serious eye irritation.
 - H411 Toxic to aquatic life with long lasting effects.
 - H412 Harmful to aquatic life with long lasting effects.
 - EUH205 Contains epoxy constituents. May produce an allergic reaction.
- Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Skin corrosion/irritation Serious eye damage/irritation Skin sensitisation Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
---	--

- Department issuing SDS: Research and Development
- Contact: Saïda El Asjadi, tel: +31 182 372177, e-mail: safety@de-ijssel-coatings.nl
- Date of previous version: 28.01.2022
- Version number of previous version: 51
- Abbreviations and acronyms:
 - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 - ICAO: International Civil Aviation Organisation
 - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - VOC: Volatile Organic Compounds (USA, EU)
 - DNEL: Derived No-Effect Level (REACH)
 - PNEC: Predicted No-Effect Concentration (REACH)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - Skin Irrit. 2: Skin corrosion/irritation – Category 2
 - Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 - Skin Sens. 1: Skin sensitisation – Category 1
 - Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
 - Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
- Sources: Literature data and/or investigation reports are available through the manufacturer.
- * Data compared to the previous version altered.