

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: IJMODUR BM

Article number: 432

UFI: 06H4-30JG-F00S-WWGQ

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
 SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU19 Building and construction work

Product category PC9a Coatings and paints, thinners, paint removers

Process category PROC19 Manual activities involving hand contact

PROC7 Industrial spraying

PROC10 Roller application or brushing

PROC11 Non industrial spraying

Environmental release category ERC5 Use at industrial site leading to inclusion into/onto article

ERC8c Widespread use leading to inclusion into/onto article (indoor)

ERC8f Widespread use leading to inclusion into/onto article (outdoor)

Article category AC13 Plastic articles

AC11 Wood articles

Application of the substance / the mixture See our technical datasheet for application details of this product.
 Clear coating material, Varnish

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: De IJssel Coatings BV, Centrumbaan 960, NL 2841 MH Moordrecht
 Tel: +31 182 372177, E-mail: info@de-ijssel-coatings.nl

Further information obtainable from: Research and Development.


1.4 Emergency telephone number:

De IJssel Coatings BV, Tel. +31 182 372177, E-mail: safety@de-ijssel-coatings.nl
 Office hours: working days from 08:00 to 17:00 hrs.


SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

 GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.

 GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

 GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

  
 GHS02 GHS07 GHS08

Signal word Danger

Hazard-determining components of labelling:

Aromatisch polyisocyanaat
 n-butyl acetate
 m-tolylidene diisocyanate

Hazard statements H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

(Contd. on page 2)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 45 (replaces version 44)

Revision: 13.06.2023

Trade name: IJMODUR BM

(Contd. of page 1)

<ul style="list-style-type: none"> · Precautionary statements · Additional information: · 2.3 Other hazards · Results of PBT and vPvB assessment · PBT: · vPvB: 	<p>H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness.</p> <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P284 [In case of inadequate ventilation] wear respiratory protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P405 Store locked up. P501 Dispose of contents/container in accordance with local/regional/national/international regulations.</p> <p>EUH204 Contains isocyanates. May produce an allergic reaction.</p> <p>Not applicable. Not applicable.</p>
--	---

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 103051-64-5	Aromatisch polyisocyanaat ⚠ Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH204	25 – 50%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336, EUH066	25 – 50%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	10 – 25%
CAS: 26471-62-5 EINECS: 247-722-4 Index number: 615-006-00-4 Reg.nr.: 01-2119454791-34	m-tolyldiene diisocyanate ⚠ Acute Tox. 1, H330; ⚠ Resp. Sens. 1, H334; Carc. 2, H351; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412, EUH204 Specific concentration limit: Resp. Sens. 1; H334: C ≥ 0.1 %	0.1 – 0.5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

<ul style="list-style-type: none"> · General information: · After inhalation: · After skin contact: · After eye contact: · After swallowing: · 4.2 Most important symptoms and effects, both acute and delayed · 4.3 Indication of any immediate medical attention and special treatment needed 	<p>Immediately remove any clothing soiled by the product. Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.</p> <p>Supply fresh air and to be sure call for a doctor. In case of unconsciousness place patient stably in side position for transportation.</p> <p>Immediately wash with water and soap and rinse thoroughly. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.</p> <p>If symptoms persist consult doctor.</p> <p>No further relevant information available.</p> <p>No further relevant information available.</p>
--	--

(Contd. on page 3)

Trade name: IJMODUR BM

(Contd. of page 2)

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- Suitable extinguishing agents: CO2 or powder. Fight larger fires with alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Dispose contaminated material as waste according to section 13.
 Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

* **SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
 Prevent formation of aerosols.
- Information about fire - and explosion protection: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- Storage:
- Requirements to be met by storerooms and receptacles: Store material in original, tightly closed containers in a cool, well-ventilated area in accordance with applicable (local) regulations. Depending on total volume stored, the storage area should comply with PGS15.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- Recommended storage temperature: 5 - 30 °C
- **7.3 Specific end use(s)** No further relevant information available.

* **SECTION 8: Exposure controls/personal protection**

8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:	
123-86-4 n-butyl acetate	
IOELV	Short-term value: 723 mg/m ³ , 150 ppm Long-term value: 241 mg/m ³ , 50 ppm
108-65-6 2-methoxy-1-methylethyl acetate	
IOELV	Short-term value: 550 mg/m ³ , 100 ppm Long-term value: 275 mg/m ³ , 50 ppm Skin

(Contd. on page 4)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 45 (replaces version 44)

Revision: 13.06.2023

Trade name: IJMODUR BM

(Contd. of page 3)

· DNEL (Derived No Effect Level) for workers		
123-86-4 n-butyl acetate		
Inhalative	Acute - systemic effects, worker	960 mg/m ³ (Worker)
	Acute - local effects, worker	960 mg/m ³ (Worker)
	Long-term - systemic effects, worker	480 mg/m ³ (Worker)
	Long-term - local effects, worker	480 mg/m ³ (Worker)
108-65-6 2-methoxy-1-methylethyl acetate		
Dermal	Long-term - systemic effects, worker	153.5 mg/kg bw/day (Worker)
Inhalative	Long-term - systemic effects, worker	275 mg/m ³ (Worker)
· DNEL (Derived No Effect Level) for the general population		
123-86-4 n-butyl acetate		
Inhalative	Acute - systemic effects, general population	859.7 mg/m ³ (General population)
	Acute - local effects, general population	859.7 mg/m ³ (General population)
	Long-term - systemic effects, general population	102.34 mg/m ³ (General population)
	Long-term - local effects, general population	102.34 mg/m ³ (General population)
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	Long-term - systemic effects, general population	1.67 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects, general population	54.8 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects, general population	33 mg/m ³ (General population)
· PNEC (Predicted No Effect Concentration) values		
123-86-4 n-butyl acetate		
Aquatic compartment - freshwater		0.18 mg/l (Freshwater)
Aquatic compartment - marine water		0.018 mg/l (Marine water)
Aquatic compartment - water, intermittent releases		0.36 mg/l (Intermittent release water)
Aquatic compartment - sediment in freshwater		0.981 mg/kg sed dw (Sediment freshwater)
Aquatic compartment - sediment in marine water		0.0981 mg/kg sed dw (Sediment marine water)
Terrestrial compartment - soil		0.0903 mg/kg dw (Soil)
Sewage treatment plant		35.6 mg/l (stp)
108-65-6 2-methoxy-1-methylethyl acetate		
Aquatic compartment - freshwater		0.635 mg/l (Freshwater)
Aquatic compartment - marine water		0.0635 mg/l (Marine water)
Aquatic compartment - water, intermittent releases		6.35 mg/l (Intermittent release water)
Aquatic compartment - sediment in freshwater		3.29 mg/kg sed dw (Sediment freshwater)
Aquatic compartment - sediment in marine water		0.329 mg/kg sed dw (Marine water)
Terrestrial compartment - soil		0.29 mg/kg dw (Soil)
Sewage treatment plant		100 mg/l (stp)

· Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove all soiled and contaminated clothing
 - Wash hands before breaks and at the end of work.
 - Avoid contact with the eyes.
 - Avoid contact with the eyes and skin.
- Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- Hand protection
 - Protective gloves
 - The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 - Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
 - Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- Material of gloves
 - Nitrile rubber, NBR
 - The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is

(Contd. on page 5)

Trade name: IJMODUR BM

(Contd. of page 4)

- Penetration time of glove material
 - a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
 - Recommended thickness of the material: ≥ 0.3 mm
 - The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
 - For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).
- For the permanent contact gloves made of the following materials are suitable:
 - Nitrile rubber, NBR
- As protection from splashes gloves made of the following materials are suitable:
 - Nitrile rubber, NBR
- Not suitable are gloves made of the following materials:
 - Leather gloves
 - Strong material gloves
- Eye/face protection
 - Tightly sealed goggles

*** SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties	
· General Information	
· Physical state	Fluid
· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	124 – 128 °C
· Flammability	Flammable.
· Lower and upper explosion limit	
· Lower:	1.2 Vol %
· Upper:	10.8 Vol %
· Flash point:	27 °C (Pensky Martens, ASTM D93)
· Auto-ignition temperature:	315 °C
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	10.7 hPa
· Density and/or relative density	
· Density at 20 °C:	1.037 g/cm ³ (DIN 51757, ASTM D 1298)
· Relative density	Not determined.
· Vapour density	Not determined.
· 9.2 Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Solvent content:	
· Organic solvents:	52.0 %
· VOC:	
· VOC (2004/42/EC):	51.99 %
· Solids content:	48.0 %
· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Void

(Contd. on page 6)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 45 (replaces version 44)

Revision: 13.06.2023

Trade name: IJMODUR BM

(Contd. of page 5)

· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void
· Nitrogen content	4.8 %

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

*** SECTION 11: Toxicological information**

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- Acute toxicity Harmful if inhaled.
- LD/LC50 values relevant for classification:

· Components	Type	Value	Species
123-86-4 n-butyl acetate			
Oral	LD50	10,760 mg/kg	(Rat)
Dermal	LD50	> 5,000 mg/kg	(Rabbit)
108-65-6 2-methoxy-1-methylethyl acetate			
Oral	LD50	8,532 mg/kg	(Rat)

- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· Endocrine disrupting properties
None of the ingredients is listed.

*** SECTION 12: Ecological information**

- **12.1 Toxicity**
- Aquatic toxicity: No further relevant information available.

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 18.07.2023

Version number 45 (replaces version 44)

Revision: 13.06.2023

Trade name: IJMODUR BM

(Contd. of page 6)

Type of test	Effective concentration	Method	Assessment
ATE (Acute Toxicity Estimates)			
Inhalative	LC50/4 h	100 mg/l (Rat)	
123-86-4 n-butyl acetate			
Oral	EC50	44 mg/l (Daphnia magna)	
Inhalative	LC50/4 h	> 21 mg/l (Rat)	
	LC50/96 h	18 mg/l (Fish Acute Toxicity Study)	
108-65-6 2-methoxy-1-methylethyl acetate			
Inhalative	LC50/4 h	35.7 mg/l (Rat)	
26471-62-5 m-tolylidene diisocyanate			
Inhalative	LC50/4 h	0.24 mg/l (Rat)	

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- PBT: Not applicable.
- vPvB: Not applicable.
- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- Additional ecological information:
- General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue	
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 12	waste paint and varnish other than those mentioned in 08 01 11
HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP13	Sensitising

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN number or ID number	
· ADR/RID/ADN, IMDG, IATA	UN1263
· 14.2 UN proper shipping name	
· ADR/RID/ADN	1263 PAINT
· IMDG, IATA	PAINT
· 14.3 Transport hazard class(es)	
· ADR/RID/ADN	
· Class	3 (F1) Flammable liquids.
· Label	3

(Contd. on page 8)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 45 (replaces version 44)

Revision: 13.06.2023

Trade name: IJMODUR BM

(Contd. of page 7)

· IMDG, IATA · Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR/RID/ADN, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category	Warning: Flammable liquids. 30 F-E, S-E A
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR/RID/ADN · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category · Tunnel restriction code	3 D/E

· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I
None of the ingredients is listed.
- Seveso category
P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements
5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements
50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII
Conditions of restriction: 3, 74

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 18.07.2023

Version number 45 (replaces version 44)

Revision: 13.06.2023

Trade name: IJMODUR BM

(Contd. of page 8)

- National regulations:
- Technical instructions (air):

Class	Share in %
I	0.2
NK	52.0

- **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH204	Contains isocyanates. May produce an allergic reaction.

- Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Flammable liquids	On basis of test data
Acute toxicity - inhalation	Expert judgement
Serious eye damage/irritation Respiratory sensitisation Skin sensitisation Specific target organ toxicity (single exposure)	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

- Department issuing SDS:
- Contact:
- Date of previous version:
- Version number of previous version:
- Abbreviations and acronyms:

Research and Development

Saïda El Asjadi, tel: +31 182 372177, e-mail: safety@de-ijssel-coatings.nl
28.01.2022

44

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 1: Acute toxicity – Category 1

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

Literature data and/or investigation reports are available through the manufacturer.

- Sources:
- * Data compared to the previous version altered.