

18.07.2023

**Kit components**

Product code	Description
--------------	-------------

<b>457</b>	<b>Double Coat Karaat set</b>
------------	-------------------------------

Components:

455	Double Coat Karaat basis
-----	--------------------------

456	Double Coat Karaat verharder
-----	------------------------------

**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 45 (replaces version 44)

Revision: 26.06.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking


#### 1.1 Product identifier

- Trade name: **Double Coat Karaat basis**
- Article number: 455
- UFI: 6205-N0Y5-F00D-AY9V
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- Sector of Use
  - SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
  - SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
  - SU19 Building and construction work
- Product category
  - PC9a Coatings and paints, thinners, paint removers
- Process category
  - PROC19 Manual activities involving hand contact
  - PROC7 Industrial spraying
  - PROC10 Roller application or brushing
  - PROC11 Non industrial spraying
- Environmental release category
  - ERC5 Use at industrial site leading to inclusion into/onto article
  - ERC8c Widespread use leading to inclusion into/onto article (indoor)
  - ERC8f Widespread use leading to inclusion into/onto article (outdoor)
- Article category
  - AC13 Plastic articles
  - AC11 Wood articles
- Application of the substance / the mixture
  - See our technical datasheet for application details of this product.
  - Polyurethane lacquer
- **1.3 Details of the supplier of the safety data sheet**
- Manufacturer/Supplier: De IJssel Coatings BV, Centrumbaan 960, NL 2841 MH Moordrecht  
Tel: +31 182 372177, E-mail: info@de-ijssel-coatings.nl
- Further information obtainable from: Research and Development.
- **1.4 Emergency telephone number:** De IJssel Coatings BV, Tel. +31 182 372177, E-mail: safety@de-ijssel-coatings.nl  
Office hours: working days from 08:00 to 17:00 hrs.

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

- Classification according to Regulation (EC) No 1272/2008

 GHS02 flame

Flam. Liq. 3      H226 Flammable liquid and vapour.

 GHS07

Skin Sens. 1      H317 May cause an allergic skin reaction.



STOT SE 3      H336 May cause drowsiness or dizziness.

Aquatic Chronic 3      H412 Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
- Hazard pictograms

The product is classified and labelled according to the CLP regulation.

   
GHS02 GHS07

- Signal word

Warning

- Hazard-determining components of labelling:

2-ethoxy-1-methylethyl acetate  
2-methoxy-1-methylethyl acetate  
Reactionmass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacat and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacat

- Hazard statements

H226 Flammable liquid and vapour.  
H317 May cause an allergic skin reaction.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

- Precautionary statements

P101      If medical advice is needed, have product container or label at hand.  
P102      Keep out of reach of children.

(Contd. on page 2)

**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 45 (replaces version 44)

Revision: 26.06.2023

**Trade name: Double Coat Karaat basis**

(Contd. of page 1)

P103	Read carefully and follow all instructions.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P261	Avoid breathing mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

**· 2.3 Other hazards**

- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

**\* SECTION 3: Composition/information on ingredients**

**· 3.2 Mixtures**

- Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 54839-24-6 EINECS: 259-370-9 Index number: 603-177-00-8 Reg.nr.: 01-2119475116-39	2-ethoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	10 – 25%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	10 – 25%
CAS: 108-32-7 EINECS: 203-572-1 Index number: 607-194-00-1 Reg.nr.: 01-2119537232-48	propylene carbonate ⚠ Eye Irrit. 2, H319	2.910%
EC number: 915-687-0 Reg.nr.: 01-2119491304-40	Reactionmass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacat and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacat ⚠ Aquatic Acute 1, H400; ⚠ Aquatic Chronic 1, H410; ⚠ Skin Sens. 1A, H317	0.5 – 1%

- Additional information: For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**

**· 4.1 Description of first aid measures**

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.

**· 4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**· 4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures**

**· 5.1 Extinguishing media**

- Suitable extinguishing agents: CO2 or powder. Fight larger fires with alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 3)

**Trade name: Double Coat Karaat basis**

(Contd. of page 2)

- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- Protective equipment: No special measures required.

**SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

**\* SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- Storage: Requirements to be met by storerooms and receptacles: Store material in original, tightly closed containers in a cool, well-ventilated area in accordance with applicable (local) regulations. Depending on total volume stored, the storage area should comply with PGS15.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- Recommended storage temperature: 5 - 30 °C
- **7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

· Ingredients with limit values that require monitoring at the workplace:		
<b>108-65-6 2-methoxy-1-methylethyl acetate</b>		
IOELV	Short-term value: 550 mg/m <sup>3</sup> , 100 ppm Long-term value: 275 mg/m <sup>3</sup> , 50 ppm Skin	
· DNEL (Derived No Effect Level) for workers		
<b>54839-24-6 2-ethoxy-1-methylethyl acetate</b>		
Dermal	Long-term - systemic effects, worker	103 mg/kg bw/day (Worker)
Inhalative	Acute - systemic effects, worker	608 mg/m <sup>3</sup> (Worker)
	Long-term - systemic effects, worker	302 mg/m <sup>3</sup> (Worker)
<b>108-65-6 2-methoxy-1-methylethyl acetate</b>		
Dermal	Long-term - systemic effects, worker	153.5 mg/kg bw/day (Worker)
Inhalative	Long-term - systemic effects, worker	275 mg/m <sup>3</sup> (Worker)

(Contd. on page 4)

**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 45 (replaces version 44)

Revision: 26.06.2023

**Trade name: Double Coat Karaat basis**

(Contd. of page 3)

<b>108-32-7 propylene carbonate</b>		
Dermal	Long-term - systemic effects, worker	50 mg/kg bw/day (Worker)
Inhalative	Long-term - systemic effects, worker	176 mg/m <sup>3</sup> (Worker)
	Long-term - local effects, worker	20 mg/m <sup>3</sup> (Worker)
<b>Reactionmass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacat and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacat</b>		
Dermal	Acute - systemic effects, worker	2.5 mg/kg bw/day (Worker)
Inhalative	Acute - systemic effects, worker	2.35 mg/m <sup>3</sup> (Worker)
	Long-term - systemic effects, worker	2.35 mg/m <sup>3</sup> (Worker)
· DNEL (Derived No Effect Level) for the general population		
<b>54839-24-6 2-ethoxy-1-methylethyl acetate</b>		
Oral	Long-term - systemic effects, general population	13.1 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects, general population	62 mg/kg bw/day (General population)
Inhalative	Acute - systemic effects, general population	365 mg/m <sup>3</sup> (General population)
	Long-term - systemic effects, general population	181 mg/m <sup>3</sup> (General population)
<b>108-65-6 2-methoxy-1-methylethyl acetate</b>		
Oral	Long-term - systemic effects, general population	1.67 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects, general population	54.8 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects, general population	33 mg/m <sup>3</sup> (General population)
<b>108-32-7 propylene carbonate</b>		
Oral	Long-term - systemic effects, general population	25 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects, general population	25 mg/kg bw/day (General population)
Inhalative	Long-term - local effects, general population	10 mg/m <sup>3</sup> (General population)
<b>Reactionmass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacat and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacat</b>		
Oral	Acute - systemic effects, general population	1.25 mg/kg bw/day (General population)
	Long-term - systemic effects, general population	1.25 mg/kg bw/day (General population)
Dermal	Acute - systemic effects, general population	1.25 mg/kg bw/day (General population)
	Long-term - systemic effects, general population	1.25 mg/kg bw/day (General population)
Inhalative	Acute - systemic effects, general population	0.58 mg/m <sup>3</sup> (General population)
	Long-term - systemic effects, general population	0.58 mg/m <sup>3</sup> (General population)
· PNEC (Predicted No Effect Concentration) values		
<b>54839-24-6 2-ethoxy-1-methylethyl acetate</b>		
Aquatic compartment - freshwater		1.3 mg/l
Aquatic compartment - marine water		0.13 mg/l
Aquatic compartment - sediment in freshwater		6.4 mg/kg sed dw
Aquatic compartment - sediment in marine water		1.34 mg/kg sed dw
Terrestrial compartment - soil		1.34 mg/kg dw
Sewage treatment plant		62.5 mg/l
<b>108-65-6 2-methoxy-1-methylethyl acetate</b>		
Aquatic compartment - freshwater		0.635 mg/l (Freshwater)
Aquatic compartment - marine water		0.0635 mg/l (Marine water)
Aquatic compartment - water, intermittent releases		6.35 mg/l (Intermittent release water)
Aquatic compartment - sediment in freshwater		3.29 mg/kg sed dw (Sediment freshwater)
Aquatic compartment - sediment in marine water		0.329 mg/kg sed dw (Marine water)
Terrestrial compartment - soil		0.29 mg/kg dw (Soil)
Sewage treatment plant		100 mg/l (stp)
<b>108-32-7 propylene carbonate</b>		
Aquatic compartment - freshwater		0.9 mg/l (Freshwater)
Aquatic compartment - marine water		0.09 mg/l (Marine water)
Aquatic compartment - water, intermittent releases		9 mg/l (Intermittent release water)
Terrestrial compartment - soil		0.81 mg/kg dw (Soil)

(Contd. on page 5)

**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 45 (replaces version 44)

Revision: 26.06.2023

**Trade name: Double Coat Karaat basis**

(Contd. of page 4)

Sewage treatment plant	7,400 mg/l (stp)
<b>Reactionmass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacat and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacat</b>	
Aquatic compartment - freshwater	0.0022 mg/l (Freshwater)
Aquatic compartment - marine water	0.00022 mg/l (Marine water)
Aquatic compartment - water, intermittent releases	0.009 mg/l (Intermittent release water)
Aquatic compartment - sediment in freshwater	1.05 mg/kg sed dw (Sediment freshwater)
Aquatic compartment - sediment in marine water	0.11 mg/kg sed dw (Sediment marine water)
Terrestrial compartment - soil	0.21 mg/kg dw (Soil)
Sewage treatment plant	1 mg/l (stp)

- Additional information: The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:
  - Immediately remove all soiled and contaminated clothing
  - Wash hands before breaks and at the end of work.
- Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- Hand protection: Protective gloves  
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- Material of gloves: Nitrile rubber, NBR  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.  
Recommended thickness of the material:  $\geq 0.3$  mm
- Penetration time of glove material: The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.  
For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).
- For the permanent contact gloves made of the following materials are suitable: Nitrile rubber, NBR
- As protection from splashes gloves made of the following materials are suitable: Nitrile rubber, NBR
- Not suitable are gloves made of the following materials: Leather gloves  
Strong material gloves
- Eye/face protection: Tightly sealed goggles

**\* SECTION 9: Physical and chemical properties**

<b>· 9.1 Information on basic physical and chemical properties</b>	
· General Information	
· Physical state	Fluid
· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	146 °C
· Flammability	Flammable.
· Lower and upper explosion limit	
· Lower:	1.5 Vol %
· Upper:	10.8 Vol %
· Flash point:	44 °C (Pensky Martens, ASTM D93)

(Contd. on page 6)

**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 45 (replaces version 44)

Revision: 26.06.2023

**Trade name: Double Coat Karaat basis**

(Contd. of page 5)

<ul style="list-style-type: none"> <li>· Auto-ignition temperature: 315 °C</li> <li>· Decomposition temperature: Not determined.</li> <li>· pH at 20 °C: 7</li> <li>· Viscosity:</li> <li>· Kinematic viscosity: Not determined.</li> <li>· Dynamic: Not determined.</li> <li>· Solubility</li> <li>· water: Not miscible or difficult to mix.</li> <li>· Partition coefficient n-octanol/water (log value): Not determined.</li> <li>· Vapour pressure at 20 °C: 3.4 hPa</li> <li>· Density and/or relative density</li> <li>· Density at 20 °C: 1.079 g/cm<sup>3</sup> (DIN 51757, ASTM D 1298)</li> <li>· Relative density: Not determined.</li> <li>· Vapour density: Not determined.</li> </ul>	
<p><b>· 9.2 Other information</b></p> <ul style="list-style-type: none"> <li>· Appearance:</li> <li>· Form: Fluid</li> <li>· Important information on protection of health and environment, and on safety.</li> <li>· Ignition temperature: Product is not selfigniting.</li> <li>· Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.</li> <li>· Solvent content:</li> <li>· Organic solvents: 49.8 %</li> <li>· VOC:</li> <li>· VOC (2004/42/EC): 49.78 %</li> <li>· Solids content: 48.5 %</li> <li>· Change in condition</li> <li>· Evaporation rate: Not determined.</li> </ul>	
<ul style="list-style-type: none"> <li>· Information with regard to physical hazard classes</li> <li>· Explosives: Void</li> <li>· Flammable gases: Void</li> <li>· Aerosols: Void</li> <li>· Oxidising gases: Void</li> <li>· Gases under pressure: Void</li> <li>· Flammable liquids: Flammable liquid and vapour.</li> <li>· Flammable solids: Void</li> <li>· Self-reactive substances and mixtures: Void</li> <li>· Pyrophoric liquids: Void</li> <li>· Pyrophoric solids: Void</li> <li>· Self-heating substances and mixtures: Void</li> <li>· Substances and mixtures, which emit flammable gases in contact with water: Void</li> <li>· Oxidising liquids: Void</li> <li>· Oxidising solids: Void</li> <li>· Organic peroxides: Void</li> <li>· Corrosive to metals: Void</li> <li>· Desensitised explosives: Void</li> </ul>	

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

(Contd. on page 7)

**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 45 (replaces version 44)

Revision: 26.06.2023

**Trade name: Double Coat Karaat basis**

(Contd. of page 6)

**\* SECTION 11: Toxicological information**

**· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

- Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values relevant for classification:

Components	Type	Value	Species
<b>108-65-6 2-methoxy-1-methylethyl acetate</b>			
Oral	LD50	8,532 mg/kg	(Rat)
<b>108-32-7 propylene carbonate</b>			
Oral	LD50	29,000 mg/kg	(Rat)

- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

**· 11.2 Information on other hazards**

· Endocrine disrupting properties
None of the ingredients is listed.

**\* SECTION 12: Ecological information**

**· 12.1 Toxicity**

- Aquatic toxicity: No further relevant information available.

Type of test	Effective concentration	Method	Assessment
<b>108-65-6 2-methoxy-1-methylethyl acetate</b>			
Inhalative	LC50/4 h	35.7 mg/l	(Rat)

**· 12.2 Persistence and degradability**

No further relevant information available.

**· 12.3 Bioaccumulative potential**

No further relevant information available.

**· 12.4 Mobility in soil**

No further relevant information available.

**· 12.5 Results of PBT and vPvB assessment**

- PBT: Not applicable.
- vPvB: Not applicable.

**· 12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

**· 12.7 Other adverse effects**

- Remark: Harmful to fish

· Additional ecological information:

- General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.  
Harmful to aquatic organisms

**SECTION 13: Disposal considerations**

**· 13.1 Waste treatment methods**

- Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue	
HP3	Flammable
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP14	Ecotoxic

(Contd. on page 8)

**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 45 (replaces version 44)

Revision: 26.06.2023

**Trade name: Double Coat Karaat basis**

(Contd. of page 7)

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

### SECTION 14: Transport information

· <b>14.1 UN number or ID number</b> · ADR/RID/ADN, IMDG, IATA	UN1263
· <b>14.2 UN proper shipping name</b> · ADR/RID/ADN · IMDG, IATA	1263 PAINT PAINT
· <b>14.3 Transport hazard class(es)</b> · ADR/RID/ADN · Class · Label	3 (F1) Flammable liquids. 3
· IMDG, IATA · Class · Label	3 Flammable liquids. 3
· <b>14.4 Packing group</b> · ADR/RID/ADN, IMDG, IATA	III
· <b>14.5 Environmental hazards:</b> · Marine pollutant:	No
· <b>14.6 Special precautions for user</b> · Hazard identification number (Kemler code): · EMS Number: · Stowage Category	Warning: Flammable liquids. 30 F-E, <u>S</u> -E A
· <b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable.
· Transport/Additional information: · ADR/RID/ADN · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category · Tunnel restriction code	3 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

### SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I  
None of the ingredients is listed.
- Seveso category  
P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements  
5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements  
50,000 t

(Contd. on page 9)

**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 45 (replaces version 44)

Revision: 26.06.2023

**Trade name: Double Coat Karaat basis**

(Contd. of page 8)

- REGULATION (EC) No 1907/2006  
ANNEX XVII

Conditions of restriction: 3

- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- REGULATION (EU) 2019/1148

- Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

- Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

- Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

- Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- National regulations:

- Technical instructions (air):

Class	Share in %
NK	49.8

- **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
  - H226 Flammable liquid and vapour.
  - H317 May cause an allergic skin reaction.
  - H319 Causes serious eye irritation.
  - H336 May cause drowsiness or dizziness.
  - H400 Very toxic to aquatic life.
  - H410 Very toxic to aquatic life with long lasting effects.

- Classification according to Regulation (EC) No 1272/2008
  - The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Flammable liquids	On basis of test data
Skin sensitisation Specific target organ toxicity (single exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

- Department issuing SDS: Research and Development
- Contact: Saïda El Asjadi, tel: +31 182 372177, e-mail: [safety@de-ijsse-coatings.nl](mailto:safety@de-ijsse-coatings.nl)
- Date of previous version: 23.03.2021
- Version number of previous version: 44
- Abbreviations and acronyms:
  - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
  - IMDG: International Maritime Code for Dangerous Goods
  - IATA: International Air Transport Association
  - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
  - EINECS: European Inventory of Existing Commercial Chemical Substances
  - ELINCS: European List of Notified Chemical Substances
  - CAS: Chemical Abstracts Service (division of the American Chemical Society)
  - VOC: Volatile Organic Compounds (USA, EU)
  - DNEL: Derived No-Effect Level (REACH)
  - PNEC: Predicted No-Effect Concentration (REACH)
  - LC50: Lethal concentration, 50 percent
  - LD50: Lethal dose, 50 percent
  - PBT: Persistent, Bioaccumulative and Toxic
  - vPvB: very Persistent and very Bioaccumulative
  - Flam. Liq. 3: Flammable liquids – Category 3
  - Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
  - Skin Sens. 1: Skin sensitisation – Category 1
  - Skin Sens. 1A: Skin sensitisation – Category 1A
  - STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
  - Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

(Contd. on page 10)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 45 (replaces version 44)

Revision: 26.06.2023

---

**Trade name: Double Coat Karaat basis**

---

(Contd. of page 9)

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

Literature data and/or investigation reports are available through the manufacturer.

· Sources:

· \* Data compared to the previous version altered.

---

— EU —

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

Trade name: **Double Coat Karaat verharder**

Article number: 456  
 Registration number: 01-2119488934-20  
 UFI: 9GM4-A0SK-300K-1VN5

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Sector of Use: SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites  
 SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)  
 SU19 Building and construction work  
 Product category: PC9a Coatings and paints, thinners, paint removers  
 Process category: PROC19 Manual activities involving hand contact  
 PROC7 Industrial spraying  
 PROC10 Roller application or brushing  
 PROC11 Non industrial spraying  
 Environmental release category: ERC5 Use at industrial site leading to inclusion into/onto article  
 ERC8c Widespread use leading to inclusion into/onto article (indoor)  
 ERC8f Widespread use leading to inclusion into/onto article (outdoor)  
 Article category: AC13 Plastic articles  
 AC11 Wood articles  
 Application of the substance / the mixture: See our technical datasheet for application details of this product.  
 Isocyanate hardener for polyurethanes

**1.3 Details of the supplier of the safety data sheet**

Manufacturer/Supplier: De IJssel Coatings BV, Centrumbaan 960, NL 2841 MH Moordrecht  
 Tel: +31 182 372177, E-mail: info@de-ijssel-coatings.nl

Further information obtainable from: Research and Development.

**1.4 Emergency telephone number:**

De IJssel Coatings BV, Tel. +31 182 372177, E-mail: safety@de-ijssel-coatings.nl  
 Office hours: working days from 08:00 to 17:00 hrs.

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008

 GHS07

Acute Tox. 4 H332 Harmful if inhaled.  
 Skin Sens. 1 H317 May cause an allergic skin reaction.  
 STOT SE 3 H335 May cause respiratory irritation.

**2.2 Label elements**

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

 GHS07

Signal word

Warning

Hazard-determining components of labelling:

Hexamethyleen-1,6-diisocyanat homopolymeer  
 hexamethylene-di-isocyanate

Hazard statements

H332 Harmful if inhaled.  
 H317 May cause an allergic skin reaction.  
 H335 May cause respiratory irritation.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.  
 P102 Keep out of reach of children.  
 P103 Read carefully and follow all instructions.  
 P261 Avoid breathing mist/vapours/spray.  
 P280 Wear protective gloves.  
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P312 Call a POISON CENTER/doctor if you feel unwell.  
 P362+P364 Take off contaminated clothing and wash it before reuse.

(Contd. on page 2)

**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 40 (replaces version 39)

Revision: 26.06.2023

**Trade name: Double Coat Karaat verharder**

(Contd. of page 1)

P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
 P405 Store locked up.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**· 2.3 Other hazards**

- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

**SECTION 3: Composition/information on ingredients****· 3.2 Mixtures**

- Description: Mixture of substances listed below with nonhazardous additions.

**· Dangerous components:**

CAS: 28182-81-2 NLP: 500-060-2 Reg.nr.: 01-2119488934-20	Hexamethyleen-1,6-diisocyanat homopolymeer ⚠ Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335	50 – 100%
CAS: 822-06-0 EINECS: 212-485-8 Index number: 615-011-00-1 Reg.nr.: 01-2119457571-37	hexamethylene-di-isocyanate ⚠ Acute Tox. 3, H311; Acute Tox. 2, H330; ⚠ Resp. Sens. 1, H334; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Resp. Sens. 1; H334: C ≥ 0.5 % Skin Sens. 1; H317: C ≥ 0.5 %	≤ 0.1%

- Additional information: For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures****· 4.1 Description of first aid measures**

- General information: Immediately remove any clothing soiled by the product. Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- After inhalation: Supply fresh air and to be sure call for a doctor. In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.

**· 4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**· 4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures****· 5.1 Extinguishing media**

- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

**· 5.2 Special hazards arising from the substance or mixture**

No further relevant information available.

**· 5.3 Advice for firefighters**

- Protective equipment: Mouth respiratory protective device.

**SECTION 6: Accidental release measures****· 6.1 Personal precautions, protective equipment and emergency procedures**

Not required.

**· 6.2 Environmental precautions:**

Do not allow to enter sewers/ surface or ground water.

**· 6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
 Dispose contaminated material as waste according to section 13.  
 Ensure adequate ventilation.

(Contd. on page 3)

**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 40 (replaces version 39)

Revision: 26.06.2023

**Trade name: Double Coat Karaat verharder**

(Contd. of page 2)

- **6.4 Reference to other sections** See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- Information about fire - and explosion protection: No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- Storage: Store material in original, tightly closed containers in a cool, well-ventilated area in accordance with applicable (local) regulations. Depending on total volume stored, the storage area should comply with PGS15.
- Requirements to be met by storerooms and receptacles: Store material in original, tightly closed containers in a cool, well-ventilated area in accordance with applicable (local) regulations. Depending on total volume stored, the storage area should comply with PGS15.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- Recommended storage temperature: 5 - 30 °C
- **7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

- **8.1 Control parameters**
- Ingredients with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNEL (Derived No Effect Level) for workers		
<b>28182-81-2 Hexamethyleen-1,6-diisocyaan-1,6-homopolymeer</b>		
Inhalative	Acute - local effects, worker	1 mg/m <sup>3</sup> (Worker)
	Long-term - local effects, worker	0.5 mg/m <sup>3</sup> (Worker)
<b>822-06-0 hexamethylene-di-isocyanate</b>		
Inhalative	Acute - systemic effects, worker	0.07 mg/m <sup>3</sup> (Worker)
	Long-term - systemic effects, worker	0.035 mg/m <sup>3</sup> (Worker)
	Long-term - local effects, worker	0.035 mg/m <sup>3</sup> (Worker)
· PNEC (Predicted No Effect Concentration) values		
<b>28182-81-2 Hexamethyleen-1,6-diisocyaan-1,6-homopolymeer</b>		
Aquatic compartment - freshwater		0.199 mg/l (Freshwater)
Aquatic compartment - marine water		0.0199 mg/l (Marine water)
Aquatic compartment - sediment in freshwater		44,551 mg/kg sed dw (Sediment freshwater)
Aquatic compartment - sediment in marine water		4,455 mg/kg sed dw (Sediment marine water)
Terrestrial compartment - soil		8,884 mg/kg dw (Soil)
Sewage treatment plant		100 mg/l (stp)
<b>822-06-0 hexamethylene-di-isocyanate</b>		
Aquatic compartment - freshwater		0.0774 mg/l (Freshwater)
Aquatic compartment - marine water		0.00774 mg/l (Marine water)
Aquatic compartment - sediment in freshwater		0.01334 mg/kg sed dw (Sediment freshwater)
Aquatic compartment - sediment in marine water		0.001334 mg/kg sed dw (Sediment marine water)
Terrestrial compartment - soil		0.0026 mg/kg dw (Soil)
Sewage treatment plant		8.42 mg/l (stp)

- Additional information: The lists valid during the making were used as basis.

- **8.2 Exposure controls**
- Appropriate engineering controls No further data; see section 7.

(Contd. on page 4)

**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 40 (replaces version 39)

Revision: 26.06.2023

**Trade name: Double Coat Karaat verharder**

(Contd. of page 3)

- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:
  - Keep away from foodstuffs, beverages and feed.
  - Immediately remove all soiled and contaminated clothing
  - Wash hands before breaks and at the end of work.
- Respiratory protection:
  - In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- Hand protection
  - Protective gloves
  - The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
  - Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
  - Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- Material of gloves
  - Nitrile rubber, NBR
  - The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
  - Recommended thickness of the material:  $\geq 0.3$  mm
- Penetration time of glove material
  - The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
  - For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).
- For the permanent contact gloves made of the following materials are suitable:
  - Nitrile rubber, NBR
- As protection from splashes gloves made of the following materials are suitable:
  - Nitrile rubber, NBR
- Not suitable are gloves made of the following materials:
  - Leather gloves
  - Strong material gloves
- Eye/face protection
  - Goggles recommended during refilling

**SECTION 9: Physical and chemical properties**

**· 9.1 Information on basic physical and chemical properties**

- General Information
- Physical state: Fluid
- Colour: Colourless
- Odour: Characteristic
- Odour threshold: Not determined.
- Melting point/freezing point: Undetermined.
- Boiling point or initial boiling point and boiling range: Undetermined.
- Flammability: Not applicable.
- Lower and upper explosion limit
- Lower: Not determined.
- Upper: Not determined.
- Flash point: 149 °C (Pensky Martens, ASTM D93)
- Decomposition temperature: Not determined.
- pH at 20 °C: 7
- Viscosity:
- Kinematic viscosity: Not determined.
- Dynamic at 20 °C: 2,000 mPas (Brookfield, ASTM D1544)
- Solubility
- water: Not miscible or difficult to mix.
- Partition coefficient n-octanol/water (log value): Not determined.
- Vapour pressure at 20 °C: < 0.1 hPa
- Density and/or relative density
- Density at 20 °C: 1.12 g/cm<sup>3</sup> (DIN 51757, ASTM D 1298)
- Relative density: Not determined.
- Vapour density: Not determined.

(Contd. on page 5)

**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 40 (replaces version 39)

Revision: 26.06.2023

**Trade name: Double Coat Karaat verharder**

(Contd. of page 4)

<b>· 9.2 Other information</b>	
· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· VOC:	
· VOC (2004/42/EC):	0.00 %
· Solids content:	99.8 %
· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- Acute toxicity Harmful if inhaled.
- LD/LC50 values relevant for classification:

Components	Type	Value	Species
<b>822-06-0 hexamethylene-di-isocyanate</b>			
Oral	LD50	738 mg/kg	(Rat)
Dermal	LD50	593 mg/kg	(Rat)

- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause respiratory irritation.
- STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 6)

**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 40 (replaces version 39)

Revision: 26.06.2023

**Trade name: Double Coat Karaat verharder**

(Contd. of page 5)

- Aspiration hazard Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· Endocrine disrupting properties
None of the ingredients is listed.

**SECTION 12: Ecological information**

- **12.1 Toxicity**
- Aquatic toxicity: No further relevant information available.

· Type of test	Effective concentration	Method	Assessment
<b>ATE (Acute Toxicity Estimates)</b>			
Inhalative	LC50/4 h	11 mg/l	

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**

- PBT: Not applicable.
- vPvB: Not applicable.

- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.

- **12.7 Other adverse effects**

- Additional ecological information:

- General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

**SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**

- Recommendation: Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue	
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP13	Sensitising

- Uncleaned packaging:

- Recommendation: Disposal must be made according to official regulations.

**\* SECTION 14: Transport information**

· <b>14.1 UN number or ID number</b>	Void
· ADR/RID/ADN, ADN, IMDG, IATA	
· <b>14.2 UN proper shipping name</b>	Void
· ADR/RID/ADN, ADN, IMDG, IATA	
· <b>14.3 Transport hazard class(es)</b>	Void
· ADR/RID/ADN, ADN, IMDG, IATA	
· Class	
· <b>14.4 Packing group</b>	Void
· ADR/RID/ADN, ADN, IMDG, IATA	
· <b>14.5 Environmental hazards:</b>	No
· Marine pollutant:	

(Contd. on page 7)



**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 40 (replaces version 39)

Revision: 26.06.2023

**Trade name: Double Coat Karaat verharder**

(Contd. of page 7)

IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
VOC: Volatile Organic Compounds (USA, EU)  
DNEL: Derived No-Effect Level (REACH)  
PNEC: Predicted No-Effect Concentration (REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Acute Tox. 3: Acute toxicity – Category 3  
Acute Tox. 2: Acute toxicity – Category 2  
Acute Tox. 4: Acute toxicity – Category 4  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
Resp. Sens. 1: Respiratory sensitisation – Category 1  
Skin Sens. 1: Skin sensitisation – Category 1  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· Sources:

· \* Data compared to the previous version altered.

Literature data and/or investigation reports are available through the manufacturer.