

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Silkgloss PU varnish**
 Article number: 706
 UFI: V8X3-A09H-F00C-NJQ7

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use: No further relevant information available.
 SU21 Consumer uses: Private households / general public / consumers
 SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
 SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
 SU19 Building and construction work
 PC9a Coatings and paints, thinners, paint removers
 PROC19 Manual activities involving hand contact
 Environmental release category: ERC5 Use at industrial site leading to inclusion into/onto article
 ERC8c Widespread use leading to inclusion into/onto article (indoor)
 ERC8f Widespread use leading to inclusion into/onto article (outdoor)
 Article category: AC13 Plastic articles
 AC11 Wood articles
 Application of the substance / the mixture: See our technical datasheet for application details of this product.
 Lacquer

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: De IJssel Coatings BV, Centrumbaan 960, NL 2841 MH Moordrecht
 Tel: +31 182 372177, E-mail: info@de-ijssel-coatings.nl

Further information obtainable from: Research and Development.


1.4 Emergency telephone number:

De IJssel Coatings BV, Tel. +31 182 372177, E-mail: safety@de-ijssel-coatings.nl
 Office hours: working days from 08:00 to 17:00 hrs.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

 GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.

 GHS07



STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

 
 GHS02 GHS07

Signal word

Warning

Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated heavy
 H226 Flammable liquid and vapour.

Hazard statements

H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P103 Read carefully and follow all instructions.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
 P261 Avoid breathing mist/vapours/spray.
 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

(Contd. on page 2)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 34 (replaces version 33)

Revision: 18.07.2023

Trade name: Silk gloss PU varnish

(Contd. of page 1)

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.
Rinse skin with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Additional information:

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients**· 3.2 Mixtures**

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 64742-48-9 EC number: 919-857-5 Index number: 649-327-00-6 Reg.nr.: 01-2119463258-33	Naphtha (petroleum), hydrotreated heavy ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ STOT SE 3, H336	25 – 50%
CAS: 64742-48-9 EC number: 918-481-9 Index number: 649-327-00-6 Reg.nr.: 01-2119457273-39	Naphtha (petroleum), hydrotreated heavy ⚠ Asp. Tox. 1, H304	3 – 10%
CAS: 84961-74-0 EINECS: 284-664-9 Reg.nr.: 01-2119985163-33	Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs., compds. with 2-propanamine ⚠ Skin Irrit. 2, H315; ⚠ Eye Irrit. 2, H319; ⚠ Aquatic Chronic 3, H412	3 – 10%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**· 4.1 Description of first aid measures**

· General information: Immediately remove any clothing soiled by the product.

· After inhalation: Supply fresh air; consult doctor in case of complaints.

· After skin contact: Immediately rinse with water.

· After eye contact: Rinse opened eye for several minutes under running water.

· After swallowing: If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**· 5.1 Extinguishing media**

· Suitable extinguishing agents: CO2 or powder. Fight larger fires with alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents: Water with full jet

· **5.2 Special hazards arising from the substance or mixture** No further relevant information available.**· 5.3 Advice for firefighters**

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures**· 6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 34 (replaces version 33)

Revision: 18.07.2023

Trade name: Silk gloss PU varnish

(Contd. of page 2)

- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- Information about fire - and explosion protection: Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- Storage: Store material in original, tightly closed containers in a cool, well-ventilated area in accordance with applicable (local) regulations. Depending on total volume stored, the storage area should comply with PGS15.
- Requirements to be met by storerooms and receptacles: Store material in original, tightly closed containers in a cool, well-ventilated area in accordance with applicable (local) regulations. Depending on total volume stored, the storage area should comply with PGS15.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- Recommended storage temperature: 5 - 30 °C
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- Ingredients with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- Additional information: The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures: Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
- Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- Hand protection Protective gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- Material of gloves Nitrile rubber, NBR
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
Recommended thickness of the material: ≥ 0.3 mm
- Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).

(Contd. on page 4)

Trade name: Silk gloss PU varnish

(Contd. of page 3)

- For the permanent contact gloves made of the following materials are suitable: Nitrile rubber, NBR
- As protection from splashes gloves made of the following materials are suitable: Nitrile rubber, NBR
- Not suitable are gloves made of the following materials: Leather gloves
Strong material gloves
- Eye/face protection Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

- General Information
- Physical state Fluid
- Colour: According to product specification
- Odour: Characteristic
- Odour threshold: Not determined.
- Melting point/freezing point: Undetermined.
- Boiling point or initial boiling point and boiling range 180 °C
- Flammability Flammable.
- Lower and upper explosion limit
- Lower: 0.6 Vol %
- Upper: 7 Vol %
- Flash point: 40 °C (Pensky Martens, ASTM D93)
- Auto-ignition temperature: 240 °C
- Decomposition temperature: Not determined.
- pH at 20 °C 7
- Viscosity:
- Kinematic viscosity at 40 °C 1,085 mm²/s
- Dynamic at 20 °C: 900 mPas (Brookfield, ASTM D1544)
- Solubility
- water: Not miscible or difficult to mix.
- Partition coefficient n-octanol/water (log value) Not determined.
- Vapour pressure at 20 °C: 1 hPa
- Density and/or relative density
- Density at 20 °C: 0.922 g/cm³ (DIN 51757, ASTM D 1298)
- Relative density Not determined.
- Vapour density Not determined.

· 9.2 Other information

- Appearance:
- Form: Fluid
- Important information on protection of health and environment, and on safety.
- Ignition temperature: Product is not selfigniting.
- Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- VOC:
- VOC (2004/42/EC): 43.00 %
- Solids content: 52.0 %
- Change in condition
- Evaporation rate Not determined.

- Information with regard to physical hazard classes
- Explosives Void
- Flammable gases Void
- Aerosols Void
- Oxidising gases Void
- Gases under pressure Void
- Flammable liquids Flammable liquid and vapour.
- Flammable solids Void
- Self-reactive substances and mixtures Void
- Pyrophoric liquids Void
- Pyrophoric solids Void

(Contd. on page 5)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 34 (replaces version 33)

Revision: 18.07.2023

Trade name: Silk gloss PU varnish

(Contd. of page 4)

· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values relevant for classification:

Components	Type	Value	Species
64742-48-9 Naphtha (petroleum), hydrotreated heavy			
Oral	LD50	> 5,000 mg/kg	(Rat)
Dermal	LD50	> 3,000 mg/kg	(rab)
64742-48-9 Naphtha (petroleum), hydrotreated heavy			
Oral	LD50	> 5,000 mg/kg	(Rat)
Dermal	LD50	> 3,000 mg/kg	(rab)

- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

· Endocrine disrupting properties	None of the ingredients is listed.
-----------------------------------	------------------------------------

SECTION 12: Ecological information

- **12.1 Toxicity**
- Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- PBT: Not applicable.
- vPvB: Not applicable.
- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.

(Contd. on page 6)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 34 (replaces version 33)

Revision: 18.07.2023

Trade name: Silk gloss PU varnish

(Contd. of page 5)

- **12.7 Other adverse effects**
- Additional ecological information:
- General notes:
 - Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
 - Do not allow product to reach ground water, water course or sewage system, even in small quantities.
 - Danger to drinking water if even extremely small quantities leak into the ground.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- Recommendation: Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue	
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP3	Flammable
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN number or ID number	
· ADR/RID/ADN, IMDG, IATA	UN1263
· 14.2 UN proper shipping name	
· ADR/RID/ADN	1263 PAINT
· IMDG, IATA	PAINT
· 14.3 Transport hazard class(es)	
· ADR/RID/ADN	
· Class	3 (F1) Flammable liquids.
· Label	3
· IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR/RID/ADN, IMDG, IATA	III
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	30
· EMS Number:	F-E, S-E
· Stowage Category	A
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR/RID/ADN	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
· Remarks:	In packsize up to 450 liter exempt from ADR according ADR 2.2.3.1.5.

(Contd. on page 7)

— EU —

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 34 (replaces version 33)

Revision: 18.07.2023

Trade name: Silk gloss PU varnish

(Contd. of page 6)

· IMDG	5L
· Limited quantities (LQ)	Code: E1
· Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· Remarks:	In packaging up to 30 litres exempt according to IMDG 2.3.2.5.
· UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I
None of the ingredients is listed.
- Seveso category
P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements
5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements
50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII
Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

· Classification according to Regulation (EC) No 1272/2008
The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Flammable liquids	On basis of test data
Specific target organ toxicity (single exposure)	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

- Department issuing SDS: Research and Development
- Contact: Saïda El Asjadi, tel: +31 182 372177, e-mail: safety@de-ijssel-coatings.nl
- Date of previous version: 28.01.2022
- Version number of previous version: 33

(Contd. on page 8)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 34 (replaces version 33)

Revision: 18.07.2023

Trade name: Silk gloss PU varnish

(Contd. of page 7)

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer
(Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
Literature data and/or investigation reports are available through the manufacturer.

· Sources:

- * Data compared to the previous version altered.